

Easy Operation and Numerous Uses Are Constants For This 1/8 DIN Ramping Controller



The Watlow SERIES 982 vertical 1/8 DIN-ramping controller and its companion, the horizontal SERIES 981, offer four-file / 24-step program capability, or easy-to-use non-ramping set point operation. The controller is designed with most typical programming needs in mind. The SERIES 981/982 is among the most easy-to-use ramping controllers.

Ramping operations include four files with six steps in each file. Programming options include ramp-rate or time-based profiles, guaranteed soak deviation, program looping and program status selection after power outage. The files may be linked to create a single 24-step program.

The primary analog input accepts 11 different thermocouple types, RTD or scalable process inputs. A second analog input can be factory configured for a slidewire feedback input common in gas valve control. With up to two event inputs, the SERIES 981/982 offers remote program start or hold capability and allows the operator to program a wait-for event.

The SERIES 981/982 is packaged with a NEMA 4X front panel to withstand harsh environments, four inch case depth and touch-safe wiring terminal.

The SERIES 981/982 features a three-year warranty and four day shipment, on all model, in limited quantities.

Your Authorized Watlow Distributor is:

Features and Benefits

Four files / 24 steps

- Designed to meet the needs of most ramping applications

Auto-tuning

- One-step tuning of system parameters for easy operation

Optional dual auxiliary outputs

- Flexible time-based events or alarm outputs

Optional retransmit of set point or process variable

- For master programmer or chart recorder connection

Hardware and software parameter lockout options

- Provides several levels of operator security

NEMA 4X front panel

- Provides watertight corrosion resistance

10Hz sampling rate and burst-fire control

- Smooth, accurate control of the process

Slidewire feedback

- Interfaces with most slidewire input positioning devices



WATLOW

1241 Bundy Boulevard
Winona, Minnesota 55987-5580 USA
Phone: +1 (507) 454-5300
Fax: +1 (507) 452-4507
Internet: www.watlow.com
e-mail: info@watlow.com

WIN-981-0903

ISO 9001



Registered Company
Winona, Minnesota USA

North American Sales Offices: Atlanta, (770)972-4948 • Austin, (512)249-1900 • Birmingham, (205)678-2358 • Charlotte, (704)573-8446 • Chicago, (847)458-1500 • Cincinnati, (513)398-5500 • Cleveland, (330)467-1423 • Dallas, (972)620-6030 • Denver, (303)798-7778 • Detroit, (248)651-0500 • Eastern Canada, (450)433-1309 • Houston, (281)440-3074 • Indianapolis, (317)575-8932 • Kansas City, (913)897-3973 • Los Angeles, (714)935-2999 • Louisiana, (318)864-2864 • Maryland/Virginia, (215)345-8130 • Minneapolis/Manitoba, (952)892-9222 • Nashville, (615)264-6148 • New England, (603)882-1330 • New York/New Jersey/Philadelphia, (215)345-8130 • New York, Upstate, (716)438-0454 • Ontario, (905)979-3507 • Orlando, (407)351-0737 • Phoenix, (602)795-7712 • Pittsburgh, (412)322-5004 • Portland, (360)254-1009 • Raleigh/Greensboro, (336)766-9659 • St. Louis, (314)878-4600 • Sacramento, (707)425-1155 • San Diego, (714)935-2999 • San Francisco, (408)434-1894 • Seattle, (425)222-4090 • Tampa/St. Petersburg, (407)647-9052 • Tulsa, (918)496-2826 • Western Canada, (604)444-4881 • Wisconsin, North (920)993-2161 • Wisconsin, South (262)723-5990

Asian Sales Offices: Australia, +61 (39) 335-6449 • China, +86 (21) 6277-2138 • Japan, +81 (03) 5403-4688 • Korea, +82 (02) 575-9804 • Malaysia, +60 (4) 641-5977 • Singapore, +65 6773-9488 • Taiwan, +886 (0) 7-288-5168

European Sales Offices: France, +33 (01) 3073-2425 • Germany, +49 (0) 7253-9400-0 • Italy, +39 (02) 458-8841 • Sweden, +46 31 7014959 • United Kingdom, +44 (0) 115-964-0777

Latin American Sales Office: Mexico, +52 (442) 217-6235



Specifications

Control Mode

- Single input, quad output, optional retransmit of set point or process variable.
- Programmable direct- and reverse-acting control outputs.
- 4-file, 6 steps per file, time/temperature profile or fixed-set-point control.
- Ramp-rate or time-based programming.
- Selectable control status following power loss.

Agency Approvals

- CE: 89/336/EEC Electromagnetic Compatibility Directive.
EN 50081-2: 1994 Emissions.
EN 50082-2: 1994 Immunity.
- 73/23/EEC Low Voltage Directive.
EN 61010-1: 1993 Safety.
- UL® #873, C-UL® File #E43684
- NEMA 4X

Operator Interface

- Dual, four digit LED displays. Upper: 0.4 in. (10 mm). Lower: 0.3 in. (8 mm).
- Mode, Hold/Run, Display, Up and Down keys.

Sensors/Inputs

- Contact input for software function select (event input).
- Thermocouple Types B, C², D², E, J, K, N, R, S, T and Pt 2².
- RTD resolution in 1° or 0.1° RTD scales.
- Process variables: 0-20mA, 4-20mA, 0-5V[≐] (dc), 1-5V[≐] (dc), and 0-10V[≐] (dc).
- Slidewire or digital event input options.
- Sensor break protection de-energizes system for safety. Latching or non-latching.

Input Range

Specified temperature ranges represent the controller's operational span.

Thermocouple

Available with basic or universal signal conditioner

Type C ²	0 to 2316°C	(32 to 4200°F)
Type D ²	0 to 2316°C	(32 to 4200°F)
Type E	-200 to 799°C	(-328 to 1470°F)
Type J	0 to 816°C	(32 to 1500°F)
Type K	-200 to 1371°C	(-328 to 2500°F)
Type N	0 to 1300°C	(32 to 2372°F)
Type T	-200 to 399°C	(-328 to 750°F)
Pt 2 ²	0 to 1395°C	(32 to 2543°F)

Available with universal signal conditioner

Type B	870 to 1816°C	(1598 to 3300°F)
Type R	0 to 1760°C	(32 to 3200°F)
Type S	0 to 1760°C	(32 to 3200°F)

RTD Resolution (DIN or JIS)

1° (DIN)	-200 to 800°C	(-328 to 1472°F)
1° (JIS)	-200 to 630°C	(-328 to 1166°F)
0.1° (DIN and JIS)	-73.3 to 537.7°C	(-99.9 to 999.9°F)

Process

-999 to 9999 units for all: 0-5V[≐](dc); 1-5V[≐](dc); 0-10V[≐](dc); 0-20mA; and 4-20mA.

Input 2 slidewire feedback

100 to 1200Ω.

Line Voltage/Power

- 100-240V[≐](ac/dc) +10 percent, -15 percent; 50/60Hz, ±5 percent.
- 24 to 28V[≐](ac/dc) +10 percent, -15 percent; 50/60Hz, ±5 percent.
- Fused internally (factory replaceable only) Slo-Blo® type (time-lag):
2A, 250V for high voltage versions; 5A, 250V for low voltage versions.
- Power consumption 16VA maximum.
- Non-volatile memory retains data if power fails.

Operating Environment

- 0 to 55°C (32 to 130°F), 0 to 90 percent RH, non-condensing.

Storage Temperature

- -40 to 85°C (-40 to 185°F).

Terminals

- #6 compression universal head screws, accepts 28-14 gauge wire.

Shipping Weight

- .35 kg lbs (3.01 lbs).

Sample/Update Rates

- 1 input, PID and control outputs: 10Hz.
- 2 inputs: 5Hz.
- Display: 2Hz.
- Retransmit, remote set point and alarm outputs: 1Hz.

^① Electromechanical relays warranted for 100,000 closures only. Solid-state switching devices recommended for applications requiring fast cycle times or extended service life.

^② Not an ANSI/ASTM symbol.

UL® and C-UL® are registered trademarks of the Underwriter's Laboratories, Inc.

Ordering Information

To order, complete the code number with the information below:

SERIES 981/982

Single channel 1/8 DIN ramping controller, vertical or horizontal mount

98 C -

Power Supply & Mounting

- 1 = 100 to 240V[≐](ac/dc) nominal, horizontal mounting
- 2 = 100 to 240V[≐](ac/dc) nominal, vertical mounting
- 3 = 24 to 28V[≐](ac/dc) nominal, horizontal mounting
- 4 = 24 to 28V[≐](ac/dc) nominal, vertical mounting

Software

C = Standard (4-file, 6 step per file, program capability)

Input 1

- 1 = Basic thermocouple signal conditioner (excluding Type B, R, and S)
- 2 = Universal signal conditioner (see range information)

Input 2

- 0 = None
- 3 = Slidewire feedback (see range information)
- 5 = Second digital event (one digital event is standard on all units)

Output 1

- B = Solid-state relay, Form A, 0.5A, with RC suppression
- C = Switched dc or open collector, isolated
- D = Electromechanical relay^①, Form C, 5A with RC suppression
- E = Electromechanical relay^①, Form C, 5A without RC suppression
- F = Universal process, 0-5V[≐](dc), 1-5V[≐](dc), 0-10V[≐](dc), 0-20mA, 4-20mA, isolated
- K = Solid-state relay, Form A, 0.5A, without RC suppression

Output 2

- A = None
- B = Solid-state relay, Form A, 0.5A, with RC suppression
- C = Switched dc or open collector, isolated
- D = Electromechanical relay^①, Form C, 5A with RC suppression
- E = Electromechanical relay^①, Form C, 5A without RC suppression
- F = Universal process 0-5V[≐](dc), 1-5V[≐](dc), 0-10V[≐](dc), 0-20mA, 4-20mA, isolated
- K = Solid-state relay, Form A, 0.5A, without RC suppression
- T = External signal conditioner power supply, 5, 12 or 20V[≐](dc) @ 30mA

Output 3

- A = None
- B = Solid-state relay, Form A, 0.5A, with RC suppression
- C = Switched dc, isolated
- J = Electromechanical relay^①, Form A or B, 5A without RC suppression
- K = Solid-state relay, Form A, 0.5A, without RC suppression
- M = Retransmit, 0-20mA[≐](dc), 4-20mA[≐](dc)
- N = Retransmit, 0-5V[≐](dc), 1-5V[≐](dc), 0-10V[≐](dc)
- T = External signal conditioner power supply, 5, 12 or 20V[≐](dc) @ 30mA

Output 4

- A = None
- B = Solid-state relay, Form A, 0.5A, with RC suppression
- C = Switched dc or open collector, isolated
- D = Electromechanical relay^①, Form C, 5A with RC suppression
- E = Electromechanical relay^①, Form C, 5A without RC suppression
- K = Solid-state relay, Form A, 0.5A, without RC suppression
- R = EIA/TIA-232 communications, opto-isolated
- U = EIA/TIA-232, EIA/TIA-485 communications, opto-isolated
- S = EIA/TIA-485, EIA/TIA-422 communications, opto-isolated
- T = External signal conditioner power supply, 5, 12 or 20V[≐](dc) @ 30mA

Display Color (Upper/Lower)

- GG = Green/Green RG = Red/Green
- GR = Green/Red RR = Red/Red