




OIL PUMPS

CHOOSING A GPI OIL PUMP

GPI Oil Pumps are specifically designed for use with high viscosity fluids like oil. These weatherproof pumps will give you years of service when used with the correct fluids. Consider the viscosity of the fluid being pumped and the temperature range when choosing the best

 <p>PUMP SPECS</p>		
MODEL	L 5016*	P-200-BV
PART NUMBER	142100-03	118000-9
VOLTAGE & TYPE	12-Volt DC Aluminum Housing - Gerotor Gear	12-Volt DC Molded Plastic Housing - Gear
FLOWRATE	Up to 16 QPM (15 LPM)	Up to 8 GPM (30 LPM)
DUTY CYCLE	30 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	Minimum Gauge: 10/3 (not supplied) Do not exceed 15 ft. of cord.	Minimum Gauge: 10/3 (not supplied) Do not exceed 15 ft. of cord.
NOZZLE	3/4 in. Ball Valve Nozzle	1 in. Ball Valve Nozzle
SUCTION PIPE	Two-piece	Adjustable to 40 in.
HOSE	8 ft. (2.5m) x 3/4 in.	12 ft. (3.7m) x 1 in.
MOTOR PROTECTION	Requires a 50 amp automotive-type fuse. (not supplied)	25 amp Inline Fuse (supplied)
UNIQUE FEATURE	Lightweight, rugged motor offers long life with limited maintenance.	Built-in handle with convenient Spin Collar for easy installation.
USE WITH	Oil (up to 90 wt.), waste oil, hydraulic fluid, antifreeze and non-flammable oil-based solvents.	Thin to medium lubricants up to 30 wt. oil. Do not use with gasoline or diesel fuel.
APPROVALS	Motor is UL Recognized Component and CSA Approval.	CSA Certified
WARRANTY	1 Year	2 Year