

PV411A

Four in One Hand Pump

Hydraulic pressures to 10,000 psi
Pneumatic pressures to 600 psi
Vacuum to 28.5 inHg
InH₂O range pressure generation

The PV411A is a high quality field proven pressure and vacuum hand pump providing functionality never before seen in a hand held pressure source. This remarkable product replaces four conventional hand pumps and offers the following additional features:



- Unique vacuum priming function removes trapped air during hydraulic operation
- High pressure generation is accomplished with the volume adjuster eliminating the physical effort associated with conventional hand pumps
- Pressure/Vacuum selector valve also provides exceptional fine control pressure relief in both pneumatic and hydraulic modes
- Tamper proof adjustable overpressure protection valve which can be set to relieve pressures from 300 to 10,000 psi
- Removable hydraulic reservoir which can be disconnected from the pump without draining the fluid
- Reservoir safety feature with spring loaded top cover vents if inadvertently pressurized above 8 psi
- Hydraulic mode designed to operate with distilled water and/or high viscosity mineral oil
- Highly sensitive volume adjuster is used for hydraulic, pneumatic, vacuum and low pressure operation
- Built-in stroke adjuster controls the pressure/vacuum generated per stroke
- 240° swivel head for optimum viewing of reference indicators
- Internal moving parts are Teflon anodized for reduced friction and wear
- Ergonomic, rugged and lightweight design with comfortable hand grip



GE Druck

PV411A

Four in One Hand Pump

Hydraulic pressures to 10,000 psi

Pneumatic pressures to 600 psi

Vacuum to 28.5 inHg

InH₂O range pressure generation



PV411A-HA Hand Pump Kit
(shown with DPI 705 digital pressure gauge/indicator,
not included)

SPECIFICATION

Pressure ranges: Pneumatic: 0-600 psi
Hydraulic: 0-10,000 psi
Vacuum: 0-28.5 inHg

Hydraulic media: Designed for operation with distilled water (no alcohol), mineral oil equal to 40 wt. Note: for combined hydraulic and pneumatic operations it is recommended to use distilled water during hydraulic operation.

Materials: Stainless steel, anodized aluminum, Nitrile rubber, acrylic, PTFE, polyurethane, Delrin and nylon

Pressure connections: ¼" NPT female

Reservoir connection: ¼" BSP female

Reservoir volume: 100 cc

Optional large volume reservoir: 200 cc

Total weight: 2.5 lbs.

Dimensions: 10.2" L x 5.3" W x 3.7" D

PV411A-HA Hand pump kit includes:

- Heavy duty transport case with closed foam insert
- 10,000 psi high pressure hose assembly, 3 ft. length
- 2 pcs. ¼" Male NPT adaptors
- 1 pc. ¼" Female NPT adaptor
- 1 pc. ⅛" Male NPT adaptor
- 1 pc. ⅛" Female NPT adaptor
- 1 pc. ¼" Male to ⅛" Female adaptor

ORDER CODES

PV411A- Hand pump only

PV411A-HA - Hand pump with accessory kit



GE Druck

Druck Incorporated
4 Dunham Drive, New Fairfield, CT 06812 USA
Tel: 203-746-0400, Fax: 203-746-2494
Email: usa.sales@druck.com
www.druck.com www.pressure.com